

COURTYARD LIGHTS

TS-200W-400W-600W-800W

180° Human body sensing
Single crystal high efficiency solar panels

Main Components

- Monocrystalline silicon solar panel
- High Luminous LED
- Intelligent controller
- High Quality Lithium Iron Phosphate battery



Solar Flood Light

TS Series

Parameters

| Model | TS-200W MAX | TS-400W MAX | TS-600W MAX | TS-800W MAX |
|-------------------|-------------------|------------------|------------------|------------------|
| Luminous Flux | 1500LM | 3000LM | 4500LM | 6000LM |
| Solar Panel | 20W | 40W | 50W | 65W |
| Battery Capacity | 3.2V15000mAH | 3.2V30000mAH | 3.2V45000mAH | 3.2V60000mAH |
| Lamp Size | 282*225*65mm | 342*279*65mm | 386*315*65mm | 386*315*65mm |
| Panel Size | 295*395*17mm | 530*395*17mm | 590*395*17mm | 770*395*17mm |
| Package | 8sets/case | 6sets/case | 5sets/case | 5sets/case |
| Carton Size | 503*355*247mm | 580*365*287mm | 453*355*347mm | 453*355*347mm |
| Led Chips | 144pcs LED Chips | 296pcs LED Chips | 432pcs LED Chips | 432pcs LED Chips |
| IP Grade | IP 66 | | | |
| Charging Time | 4-5H | | | |
| Working Time | 12-24H | | | |
| Color Temperature | (CW)-(6000-6500K) | | | |

Solar Pro Flood Light, The Multiple-usage Solar Light for AI



COURTYARD LIGHTS

TS-200W-400W-600W-800W

180° Human body sensing
Single crystal high efficiency solar panels

Main Components

- Monocrystalline silicon solar panel
- High Luminous LED
- Intelligent controller
- High Quality Lithium Iron Phosphate battery



Solar Flood Light

TS Series

Parameters

| Model | TS-200W POR | TS-400W POR | TS-600W POR | TS-800W POR |
|-------------------|-------------------|------------------|------------------|------------------|
| Luminous Flux | 1500LM | 3000LM | 4500LM | 6000LM |
| Solar Panel | 20W | 40W | 50W | 65W |
| Battery Capacity | 3.2V15000mAH | 3.2V30000mAH | 3.2V45000mAH | 3.2V60000mAH |
| Lamp Size | 282*225*65mm | 342*279*65mm | 386*315*65mm | 386*315*65mm |
| Panel Size | 295*395*17mm | 530*395*17mm | 590*395*17mm | 770*395*17mm |
| Package | 8sets/case | 6sets/case | 5sets/case | 5sets/case |
| Carton Size | 503*355*247mm | 580*365*287mm | 453*355*347mm | 453*355*347mm |
| Led Chips | 144pcs LED Chips | 296pcs LED Chips | 432pcs LED Chips | 432pcs LED Chips |
| IP Grade | IP 66 | | | |
| Charging Time | 4-5H | | | |
| Working Time | 12-24H | | | |
| Color Temperature | (CW)-(6000-6500K) | | | |

Solar Pro Flood Light, The Multiple-usage Solar Light for All

